




## Dimensional Drawing



LKFS MULTI-WATT AND MULTI-CCT



Model	Ø Diameter (in)	Height (in)	Weight (lb)
22L	10.6	5.5	3.7
35L	13	5.6	6

## Specifications

Model Name	AL-BE-HBRSR-22L-LKFS-U	AL-BE-HBRSR-35L-LKFS-U
Selectable Wattage (W)	97W / 118W / 150W	148W / 196W / 236W
Voltage (V)	120-277V	
Lumen Output (lm)	15,522 lm / 18,218 lm / 21,802 lm	23,920 lm / 29,953 lm / 34,621 lm
Efficacy (lm/W)	161 lm/W - 155 lm/W - 145 lm/W	52,000 lm
Color Rendering Index	80+ CRI	
Selectable Color Temp.	40 (4000K) / 50 (5000K)	
Dimming Compatible	Yes	
Longevity (L70)	146,000 hours	
Certifications/Listings	cULus, DLC, FCC	

## DESCRIPTION

Wide distribution light perfect for ceilings 20 feet and higher. Occupancy sensor ready and optimized. Long life and dimmable.

## FEATURES

- Field selectable 4000k (neutral white) and 5000k (cool white) color temperatures.
- Tri-lumen selectable delivers 16,000 to 35,000 nominal lumens.
- Screw in sensor ready. Sensor and remote control sold separately. Remote control required to change factory sensor settings.
- Long-life LEDs provide 146,000 hours of operation with at least 70% of initial lumen output (L70), and 44,000 hours with at least 90% of initial lumen output (L90).
- LED color maintenance < 0.003 chromaticity shift ( $\Delta u'v'$ ) over the initial 6,000 hours of operation.
- Color rendering index > 80.

## Ordering Guide

EG: AL-BE-HBRSR-35L-LKFS-U

Model Name	POWER	CRI	CCT	DRIVER
AL-BE-HBRSR	22L: 97W / 118W / 150W 35L: 148W / 196W / 236W	8: >80	50: 5000k	U (120-277) HV (277-480)