



LKFS MULTI-WATT AND MULTI-CCT

Dimensional Drawing



	4FT	8FT
Length - L	47.3"	94.2"
Width - W	2.4"	2.4"
Height - H	2.8"	2.8"
Weight (lbs.)	3.7	7.5

Specifications

Model Name	AL-BE-IS-5L-LKFS-U-4	AL-BE-IS-10L-LKFS-U-8
Input Wattage (W)	30W / 30W / 25W	69W / 62W / 50W
Voltage (V)	U (120-277V)	U (120-277V)
Lumen Output (lm)	4804lm / 4258lm / 3590lm	9483lm / 8440lm / 7202lm
Efficacy (lm/W)	139lm/W - 142lm/W - 144lm/W	137lm/W - 137lm/W - 144lm/W
Color Rendering Index	82+ CRI	82+ CRI
Color Temperature	35 (3500K) 40 (4000K) / 50 (5000K)	35 (3500K) 40 (4000K) / 50 (5000K)
Dimming Compatible	0-10V	0-10V
Dimensions	47.3" x 2.4" x 2.8"	94.2" x 2.4" x 2.8"
Certifications/Listings	cETLus, ETL, IP69K	cETLus, ETL, IP69K

Ordering Guide

EG: AL-BE-IS-5L-LKFS-U-4

Model Name	Lm	Driver	Length
AL-BE-IS-	5L: 5000 10L: 10000	U: Universal 120-277V HV: 277-840V	4: 4ft 8: 8ft

FEATURES

Available in 4', and 8' covered strip lights, designed as direct replacements for fluorescent strips delivering general ambient lighting in a variety of indoor settings, including schools, offices, hospitals and stores, and is the perfect choice for both new construction and retrofits with high-efficacy and uniform illumination.

FEATURES

- Long-life LEDs provide 122,000 hours of operation.
- Uniform illumination with no visible LED pixelation.
- Universal 120-277 AC voltage (50-60Hz) is standard.
- 0-10V DC dimming capability is standard.
- Color rendering index > 80.
- Steel housing and acrylic lens.
- Easy installation in new construction or retrofit
- DLC Premium approved